

K-BALGGREIFER 2,5 NBR

Bellows suction pads, round, 2.5 folds, material NBR

HANSA FLEX

Características

Características Soft, flexible folds
Soft, tapered sealing lips
Support surfaces on the bottom
high suction power
optimum damping effect
very good adaptation to curved or uneven material

Campo de aplicação Manuseio de peças extremamente irregulares
(por exemplo, tubos)
Manuseio de peças extremamente sensíveis



Nota

Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy. Outras indicações a pedido.

Descrição

Robust and hard-wearing suction pad with a single sealing lip. Used wherever objects (parts, packing materials, etc.) need to be lifted, transported, turned over or handled in some other manner. It is also ideal when it is necessary to compensate varying workpiece heights or uneven surfaces or to handle easily damaged parts. It acts as the connecting element between the vacuum generator and the workpiece.

Informações adicionais

Attention: The price does not include connection nipples. Please order separately.

Artigo

Descrição	Niple de conexão Rosca externa	Niple de conexão Rosca interna	Altura de construção com niple Rosca externa	Altura de construção com niple Rosca interna	Ø (mm)
K- 07 45 00 45	K-07450001	K-07450005	18,5	23,5	5,0
K- 07 45 00 47	K-07450002 / K-07450004	K-07450007	19 / 20	26	7,0
K- 07 45 00 49	K-07450002 / K-07450004	K-07450007	20 / 21	27	9,0
K- 07 45 00 51	K-07450002 / K-07450004	K-07450007	26 / 27	33	12,0
K- 07 45 00 53	K-07450002 / K-07450004	K-07450007	27 / 28	34	14,0
K- 07 45 00 55	K-07450002 / K-07450004	K-07450007	27 / 28	34	18,0
K- 07 45 00 57	K-07450002 / K-07450004	K-07450007	27 / 28	34	20,0
K- 07 45 00 59	K-07450004	K-07450007	40	46	25,0
K- 07 45 00 61	K-07450003	K-07450006	41,5	52,5	32,0
K- 07 45 00 63	K-07450003	K-07450006	50	61	42,0
K- 07 45 00 65	K-07450003	K-07450006	53	64	52,0

Acessórios

K-ANSCHLUSSNIP BALGSAUGER Connection nipples for bellows suction pads, round, 1.5 and 2.5 folds