

K-FEDERSTOESSEL

Spring plungers

HANSA FLEX

Características

Aplicação	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured
Temperatura min.	0 °C
Temperatura max.	80 °C
Conexão do aspirador	M 3 female
Modelo	Spring plunger with high-strength steel rod, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide
Percurso de suspensão	5,0 mm



Nota

Outras indicações a pedido.

Descrição

Suitable for all round or oval suction pads in our standard range.

Artigo

Descrição	Conexão de vácuo	Comprimento (mm)	Carga vertical (N/m2)
K- 07 45 00 73	M 3 female	33,5	550
K- 07 45 00 76	M 5 female	41,2	1500
K- 07 45 00 74	M 5 female	47,2	1500
K- 07 45 00 75	M 5 female	59,2	1500
K- 07 45 00 70	G 1/8 female	80,0	3700
K- 07 45 00 67	G 1/8 female	95,0	3700
K- 07 45 00 71	G 1/8 female	93,0	3700
K- 07 45 00 68	G 1/8 female	124,5	2400
K- 07 45 00 72	G 1/8 female	124,0	2400
K- 07 45 00 69	G 1/8 female	154,0	2400