

# K-SAUGPLATTENAUFHAENGUNG

Flexible suction pad mountings

**HANSA FLEX**

## Características

**Aplicação** For handling of workpieces with sloping using large-area vacuum gripper  
Handling of large plates that can sag when lifting  
In combination with spring plungers to compensate height-differences and Unevenness

**Características especiais** very good adaptation to oblique workpiece surfaces  
automatic Rückstellung in die Ausgangslage  
vacuum-tight design with integrated protection against damage



## Nota

Outras indicações a pedido.

## Descrição

Flexible suction pad mounting. By flexing in all directions, this mounting allows the suction pad to better adapt itself to sloping workpieces.

## Artigo

| Descrição      | Rosca 1 interna | Rosca 2 externa | H<br>(mm) | Material      | L1<br>(mm) | L2<br>(mm) | Ângulo W<br>(°) | Carga vertical<br>(N/m <sup>2</sup> ) | Momento de flexão<br>(N/m <sup>2</sup> ) | SW<br>(mm) |
|----------------|-----------------|-----------------|-----------|---------------|------------|------------|-----------------|---------------------------------------|--|------------|
| K- 07 45 01 47 | G 1/4           | M 10 x 1.25     | 27,0      | Steel, rubber | 10,5       | 8,0        | 12              | 500                                   | 8,0                                      | 17         |
| K- 07 45 01 48 | G 1/4           | G 1/4           | 27,0      | Steel, rubber | 12,0       | 12,0       | 12              | 750                                   | 10,0                                     | 17         |