

# K-DRS MDR 5 M ENTLASTU VENT

»MDR 5« pressure switches, with unloading valve / on/off switch / flange 1/4, without motor protection circuit

**HANSA FLEX**

## Características

Temperatura do fluido	-5 °C to +80 °C
pressão de desativação máx.	16 bar
Capacidade de comutação	5,5 kW
Tipo de contato	NC (3-pole)
Frequência de comutação máx.	120 (electrical), 600 (mechanical)
Tipo de proteção	IP 54



## Nota

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)  
Outras indicações a pedido.

## Descrição

Three-phase version

## Instruções de encomenda

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

## Informações adicionais

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

## Artigo

Descrição	Conexão de ar comprimido	Faixa de ajuste
K- 07 30 24 25	G 1/2	2,0 - 11,0 bar
K- 07 30 24 27	G 1/2	2,5 - 16,0 bar