
K-VERTEILER HANSA

Manifolds



Características		
Pressão de entrada	0 - 16 bar	
Faixa de temperatura	-10 °C to +50 °C	
Fluidos	Ar comprimido	
Rosca de conexão	Material: Die-cast zinc	
Carcaça	Material: Grivory® (PA 66)	





Nota

Outras indicações a pedido.

Artigo						
Descrição	Outlets	Rosca	Fluxo (L/min)	A (mm)	В	C (mm)
K- 07 25 11 17	3 x G 1/4	G 1/4	2700	52,0	65,5 mm	34,5
K- 07 25 11 18	3 x G 1/4	G 3/8	3600	52,0	65,5 mm	34,5
K- 07 25 11 19	2 x G 3/8, 1 x G 1/4, 1 x G 1/2	G 3/8	7250	63,0	80,5 mm	43,0
K- 07 25 11 20	2 x G 3/8, 1 x G 1/4, 1 x G 1/2	G 1/2	7250	63,0	80,5 mm	43,0
K- 07 25 11 21	2 x G 3/4	G 3/4	18000	85,0	109,5 mm	58,5
K- 07 25 11 22	2 x G 3/4	G 1	18000	85,0	109,5 mm	58,5

Acessório para			
K-HALTERBAUSATZ HANSA	Holder HANSA		
K-ERSATZBEHAELTER HANSA POLY	Spare tank HANSA polycarbonat		
K-GERAETESTECKER	Coupling socket		