


# K-WTEH 2-TLG PC-BEHAEL SCHUTZK MULT

Service units, 2-piece with polycarbonate bowl and bowl guard

**HANSA FLEX**

## Características

|  |  |
|--|--|
| Pressão de entrada                       | Max. 16 bar (polycarbonate bowl),<br>Max. 20 bar (metal bowl)  |
| Temperatura do fluido                    | max. 60 °C   |
| Temperatura ambiente                     | Max. 60 °C   |
| Dimensão dos poros no elemento filtrante | 5 µm (BG 1 / BG 2), 40 µm (BG 3)                               |
| Material de vedação                      | NBR  |
| Tampa da mola                            | POM-brass  |
| Carcaça                                  | Die-cast zinc, Aluminium for G 1 variant                       |
| Acessório para gotejamento               | PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)           |
| Drain valve                              | Semi-automatic   |
| Medição do valor de fluxo                | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |



## Nota

Outras indicações a pedido.

## Descrição

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

## Instruções de encomenda

2-piece service units are also available in other control ranges (0.1 - 3 bar, 0.2 - 6 bar and 0.5 - 16 bar) and in lockable version. Please ask for more information.

## Informações adicionais

1500 l/min: P1: 10 bar, P2: 7 bar,  $\Delta p \leq 0.1$  bar.

## Artigo

| Descrição      | Rosca | Faixa de regulação | Fluxo (L/min) | A (mm) | B        | C (mm) | D (mm) | DN | Tamanho |
|----------------|-------|--------------------|---------------|--------|----------|--------|--------|----|---------|
| K- 07 25 01 31 | G 1/4 | 0.5 - 10 bar       | 1100          | 92,8   | 192,1 mm | 67,0   | 125,1  | 6  | 1       |
| K- 07 25 01 34 | G 3/8 | 0.5 - 10 bar       | 1100          | 92,8   | 192,1 mm | 67,0   | 125,1  | 10 | 1       |
| K- 07 25 01 37 | G 1/2 | 0.5 - 10 bar       | 3500          | 134,8  | 246,3 mm | 99,0   | 147,3  | 15 | 2       |
| K- 07 25 01 40 | G 3/4 | 0.5 - 10 bar       | 3500          | 134,8  | 246,3 mm | 99,0   | 147,3  | 20 | 2       |
| K- 07 25 01 43 | G 1   | 0.5 - 10 bar       | 10500         | 200,0  | 381,8 mm | 128,0  | 253,8  | 25 | 3       |

## Acessório para

|                                  |                               |
|----------------------------------|-------------------------------|
| K-HALTERBAUSATZ                  | Holder                        |
| K-SCHALTTAFELMUTTER              | Nut                           |
| K-HALTERBAUSATZ MULTIFIX         | Holder                        |
| K-KOPPELPAKET MEHR               | Coupling packet               |
| K-KOPPELPAKET SCHMA              | Coupling packet               |
| K-METALLBEHAELTER OELER MULTIFIX | Metal tank oiler              |
| K-PC-BEHAELTER FILTER MULTIFIX   | Polycarbonate tank filter     |
| K-SCHUTZKORB G                   | Protective cage               |
| K-TROPFAUFSATZ POLYCARBO 1       | Drip attachment polycarbonate |
| K-TROPFAUFSATZ METALL            | Drip attachment metal         |
| K-FILTERELEMENT                  | Filter element                |
| K-AUTOMAT ABLASSVENTIL           | Automatic drain valve         |
| K-VERSCHLEI-SATZ                 | Set of wearing parts          |