
K-WKV 3/2 SCHLS SCHNVERSCHR

3/2-way toggle valves, discharge port on thread, quick-lock screw fitting

Características

Pressão operacional	máx. 8 bar
Faixa de temperatura	0 °C to +70 °C
Rosca Painel de instrumentos	M 12 x 0.75 (sheet thickness max. 4 mm)
Peças interiores	Brass with a bare metal surface
Material de vedação	NBR
Parafusos oco, braço giratório, alavanca basculante	Nickel-plated brass
Vedações (imperdíveis)	Polyamide (glass fibre-reinforced)





Nota

Outras indicações a pedido.

Descrição

Manually operated toggle valves, 2/2 and 3/2-way types. For all applications where compressed air must be switched on or off quickly and easily or a cylinder operated manually. Designed as a banjo-type valve with a hollow bolt and ring piece. Suitable for screwing directly into the equipment or for panel mounting. Compact type of construction, also ideal where space is restricted.

Artigo

Descrição	Modelo	C (mm)	para mangueira	Rosca	SW	B (mm)
K- 07 15 07 24	3/2 vias	16,0	G 1/8 IG	G 1/8	14 mm	55,0
K- 07 15 07 25	3/2 vias	25,0	5 mm / 3 mm	G 1/8	14 mm	55,0
K- 07 15 07 26	3/2 vias	25,0	6 mm / 4 mm	G 1/8	14 mm	55,0
K- 07 15 07 27	3/2 vias	25,0	8 mm / 6 mm	G 1/8	14 mm	55,0
K- 07 15 07 20	3/2 vias	22,0	G 1/4 IG	G 1/4	17 mm	60,0
K- 07 15 07 22	3/2 vias	26,5	6 mm / 4 mm	G 1/4	17 mm	60,0
K- 07 15 07 23	3/2 vias	27,5	8 mm / 6 mm	G 1/4	17 mm	60,0
K- 07 15 07 21	3/2 vias	28,5	10 mm / 8 mm	G 1/4	17 mm	60,0

Apesar de uma verificação cuidadosa, não podemos excluir a possibilidade de erros e não assumimos qualquer responsabilidade pelos dados aqui contidos.