

# K-WV 3/2 ELEKTROPNEUMATISCH

3/2-way pilot valves

**HANSA FLEX**

## Características

|                          |  |
|--------------------------|--|
| Pressão operacional      | 2,5 - 10 bar (monostable)\n1,0 - 10 bar (bistable)\nvacuum up to 10 bar (external pilot air) |
| Pressão de trabalho mín. | 2.5 bar (monostable), 1.0 bar (bistable)   |
| Faixa de temperatura     | -10 °C to +60 °C   |
| Fluxo 6bar e 10bar       | 550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2)            |
| Fluxo 6bar e 5bar        | 400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2)             |



## Nota

Outras indicações a pedido.

## Artigo

| Descrição      | Conexão | Tensão       | DN | Função     | Número do diagrama de conexões | Comando |
|----------------|---------|--------------|----|------------|--------------------------------|---------|
| K- 07 15 00 23 | G 1/8   | 24 V DC      | 5  | 3/-way NO  | 32                             |         |
| K- 07 15 00 24 | G 1/4   | 24 V DC      | 8  | 3/-way NO  | 32                             |         |
| K- 07 15 25 75 | G 3/8   | 24 V DC      | 13 | 3/-way NO  | 32                             |         |
| K- 07 15 00 25 | G 1/2"  | 24 V DC      | 15 | 3/-way NO  | 32                             |         |
| K- 07 15 00 26 | G 1/8   | 230 V, 50 Hz | 5  | 3/-way NO  | 32                             |         |
| K- 07 15 00 27 | G 1/4   | 230 V, 50 Hz | 8  | 3/-way NO  | 32                             |         |
| K- 07 15 25 76 | G 3/8   | 230 V, 50 Hz | 13 | 3/-way NO  | 32                             |         |
| K- 07 15 00 28 | G 1/2"  | 230 V, 50 Hz | 15 | 3/-way NO  | 32                             |         |
| K- 07 15 00 29 | G 1/8   | 24 V DC      | 5  | 3/2-way NC | 33                             |         |
| K- 07 15 00 30 | G 1/4   | 24 V DC      | 8  | 3/2-way NC | 33                             |         |
| K- 07 15 25 77 | G 3/8   | 24 V DC      | 13 | 3/2-way NC | 33                             |         |
| K- 07 15 00 31 | G 1/2"  | 24 V DC      | 15 | 3/2-way NC | 33                             |         |
| K- 07 15 00 32 | G 1/8   | 230 V, 50 Hz | 5  | 3/2-way NC | 33                             |         |
| K- 07 15 00 33 | G 1/4   | 230 V, 50 Hz | 8  | 3/2-way NC | 33                             |         |
| K- 07 15 25 78 | G 3/8   | 230 V, 50 Hz | 13 | 3/2-way NC | 33                             |         |
| K- 07 15 00 34 | G 1/2"  | 230 V, 50 Hz | 15 | 3/2-way NC | 33                             |         |
| K- 07 15 00 35 | G 1/8   | 24 V DC      | 5  | 3/2-way    | 34                             |         |
| K- 07 15 00 36 | G 1/4   | 24 V DC      | 8  | 3/2-way    | 34                             |         |
| K- 07 15 25 79 | G 3/8   | 24 V DC      | 13 | 3/2-way    | 34                             |         |
| K- 07 15 00 37 | G 1/2"  | 24 V DC      | 15 | 3/2-way    | 34                             |         |
| K- 07 15 00 38 | G 1/8   | 230 V, 50 Hz | 5  | 3/2-way    | 34                             |         |
| K- 07 15 00 39 | G 1/4   | 230 V, 50 Hz | 8  | 3/2-way    | 34                             |         |
| K- 07 15 25 80 | G 3/8   | 230 V, 50 Hz | 13 | 3/2-way    | 34                             |         |
| K- 07 15 00 40 | G 1/2"  | 230 V, 50 Hz | 15 | 3/2-way    | 34                             |         |