

K-WV 5/2 DIFFERENZIALKOLBEN

5/2-way pilot valves, with differential piston

HANSA FLEX

Características

Pressão operacional	2,5 - 10 bar (monostable)\n1,0 - 10 bar (bistable)\nvacuum up to 10 bar (external pilot air)
Pressão de trabalho mín.	2.5 bar (monostable), 1.0 bar (bistable)
Faixa de temperatura	-10 °C to +60 °C
Fluxo 6bar e 10bar	550 NL/min (G 1/8), 1100 NL/min (G 1/4), 2150 NL/min (G 3/8), 4600 NL/min (G 1/2)
Fluxo 6bar e 5bar	400 NL/min (G 1/8), 750 NL/min (G 1/4), 1560 NL/min (G 3/8), 3200 NL/min (G 1/2)



Nota

Outras indicações a pedido.

Artigo

Descrição	Conexão	Tensão	DN	Função	Número do diagrama de conexões	Comando
K-07 15 02 05	G 1/8	24 V DC	5	5/2-way	36	
K-07 15 02 06	G 1/4	24 V DC	8	5/2-way	36	
K-07 15 25 85	G 3/8	24 V DC	13	5/2-way	36	
K-07 15 02 07	G 1/2"	24 V DC	15	5/2-way	36	
K-07 15 02 08	G 1/8	230 V, 50 Hz	5	5/2-way	36	
K-07 15 02 09	G 1/4	230 V, 50 Hz	8	5/2-way	36	
K-07 15 25 86	G 3/8	230 V, 50 Hz	13	5/2-way	36	
K-07 15 02 10	G 1/2"	230 V, 50 Hz	15	5/2-way	36	