

K-WV 3/2 5/2 5/3 HAND

3/2, 5/2 and 5/3-way pilot valves

HANSA FLEX

Características

| | |
|----------------------|---|
| Pressão operacional | 2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar |
| Faixa de temperatura | -10 °C to +60 °C |
| Fluxo 6bar e 10bar | 550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2) |
| Fluxo 6bar e 5bar | 400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2) |
| Corpo da válvula | Alumínio |
| Mola | Special steel |
| Êmbolo | Nickel-plated aluminium |
| Material de vedação | NBR |



Nota

Outras indicações a pedido.

Artigo

| Descrição | Conexão | Função | Número do diagrama de conexões | Comando |
|----------------|---------|---------|--------------------------------|---------|
| K- 07 15 00 70 | G 1/8 | 3/2-way | 10 | |
| K- 07 15 00 71 | G 1/8 | 3/2-way | 11 | |
| K- 07 15 00 72 | G 1/4 | 3/2-way | 10 | |
| K- 07 15 00 73 | G 1/4 | 3/2-way | 11 | |
| K- 07 15 00 74 | G 1/2" | 3/2-way | 10 | |
| K- 07 15 00 75 | G 1/2" | 3/2-way | 11 | |
| K- 07 15 02 29 | G 1/8 | 5/2-way | 12 | |
| K- 07 15 02 30 | G 1/8 | 5/2-way | 13 | |
| K- 07 15 02 31 | G 1/4 | 5/2-way | 12 | |
| K- 07 15 02 32 | G 1/4 | 5/2-way | 13 | |
| K- 07 15 02 33 | G 1/2" | 5/2-way | 12 | |
| K- 07 15 02 34 | G 1/2" | 5/2-way | 13 | |
| K- 07 15 03 57 | G 1/8 | 5/3-way | 14 | |
| K- 07 15 03 58 | G 1/8 | 5/3-way | 15 | |
| K- 07 15 03 59 | G 1/8 | 5/3-way | 16 | |
| K- 07 15 03 60 | G 1/8 | 5/3-way | 17 | - |
| K- 07 15 03 61 | G 1/8 | 5/3-way | 18 | - |
| K- 07 15 03 62 | G 1/8 | 5/3-way | 19 | - |
| K- 07 15 03 63 | G 1/4 | 5/3-way | 14 | |
| K- 07 15 03 64 | G 1/4 | 5/3-way | 15 | |
| K- 07 15 03 65 | G 1/4 | 5/3-way | 16 | |
| K- 07 15 03 66 | G 1/4 | 5/3-way | 17 | - |
| K- 07 15 03 67 | G 1/4 | 5/3-way | 18 | - |
| K- 07 15 03 68 | G 1/4 | 5/3-way | 19 | - |
| K- 07 15 03 69 | G 1/2" | 5/3-way | 14 | |
| K- 07 15 03 70 | G 1/2" | 5/3-way | 15 | |
| K- 07 15 03 71 | G 1/2" | 5/3-way | 16 | |
| K- 07 15 03 72 | G 1/2" | 5/3-way | 17 | - |
| K- 07 15 03 73 | G 1/2" | 5/3-way | 18 | - |
| K- 07 15 03 74 | G 1/2" | 5/3-way | 19 | - |