K-WV 3/2 MANU L DREHHEBEL

3/2-way pilot valves, manually operated, with long wing lever, NC

Características

Pressão operacional	2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\ nMax. vacuum 10 bar (external pilot air)
Faixa de temperatura	-10 °C to +60 °C
Fluxo 6bar e 10bar	550 Nl/min
Fluxo 6bar e 5bar	400 Nl/min
Corpo da válvula	Alumínio
Mola	Special steel
Êmbolo	Aluminium
Material de vedação	NBR



Nota

3 valve positions only in conjunction with a second 3/2-way valve.
Corresponds to a 5/3-way valve.
Outras indicações a pedido.

Informações adicionais

Important: The scope of supply does not include a connector. Please order separately.

Artigo

Descrição	Conexão	Símbolo	Acionamento	Posições de comutação
K- 07 15 00 82	G 1/8	9	monostable	2
K- 07 15 00 83	G 1/8	10	dupla estabilidade	2
K- 07 15 00 84	G 1/8	11	monostable	3*
K- 07 15 00 85	G 1/8	12	dupla estabilidade	3*

Apesar de uma verificação cuidadosa, não podemos excluir a possibilidade de erros e não assumimos qualquer responsabilidade pelos dados aqui contidos.