## K-FI AK KOH METALLBEHAEL MULTIFIX

Activated carbon filters with metal bowl



Características				
Pressão de entrada	Max. 16 bar			
Temperatura do fluido	max. 60 °C			
Temperatura ambiente	Max. 60 °C			
Material de vedação	NBR			
Elemento do filtro	Activated carbon-POM			
Carcaça	Die-cast zinc			
Drain valve	Semi-automatic			
Teor de óleo residual	0.005 mg/m3			
Medição do valor de fluxo	FA at P1 = 6 bar and Δp = 0.2 bar			




133,7

34,5

15

2



## Nota

Outras indicações a pedido.

## Descrição

K- 07 25 10 52

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

Artigo								
Descrição	Rosca	Fluxo	Α	В	С	D	DN	Tamanho
		(L/min)	(mm)		(mm)	(mm)		
K- 07 25 10 49	G 1/4	380	47,8	137,0 mm	27,0	110,0	6	1

168,2 mm

68,8

Acessório para			
K-HALTERBAUSATZ MULTIFIX	Holder		
K-KOPPELPAKET MEHR	Coupling packet		
K-KOPPELPAKET SCHMA	Coupling packet		
K-PC-BEHAELTER FILTER MULTIFIX	Polycarbonate tank filter		
K-METALLBEHAELTER OELER MULTIFIX	Metal tank oiler		

1500

G 1/2