
## K-FI AK KOH METALLBEHAE MULTIFIX MI

Activated carbon filters with metal bowl



Características	
Pressão de entrada	Max. 16 bar
Temperatura do fluido	max. 60 °C
Temperatura ambiente	Max. 60 °C
Material de vedação	NBR
Elemento do filtro	Activated carbon-POM
Carcaça	Die-cast zinc
Drain valve	Semi-automatic
Teor de óleo residual	0.005 mg/m3
Medição do valor de fluxo	FA at P1 = 6 bar and pressure drop $\Delta p$ = 0.2 bar





## Nota

If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar. Outras indicações a pedido.

## Descrição

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

Art	ige	0

Descrição	Rosca	Fluxo	Α	В	С	D	DN	Tamanho
		(L/min)	(mm)		(mm)	(mm)		
K- 07 25 10 46	G 1/8	310	40,0	97,3 mm	12,3	85,0	5	0

Acessório para	
K-AUTOMAT ABLASSVENTIL	Automatic drain valve
K-KOPPELPAKET MEHR	Coupling packet
K-ERSATZBEHAELTER MULTI MINI	Spare tank »multifix-mini« & »standard-mini«