


K-FI AK KOH METALLBEHAE MULTIFIX MI

Activated carbon filters with metal bowl

HANSA FLEX

Características

| | |
|---------------------------|---|
| Pressão de entrada | Max. 16 bar |
| Temperatura do fluido | max. 60 °C |
| Temperatura ambiente | Max. 60 °C |
| Material de vedação | NBR |
| Elemento do filtro | Activated carbon-POM |
| Carcaça | Die-cast zinc |
| Drain valve | Semi-automatic |
| Teor de óleo residual | 0.005 mg/m ³ |
| Medição do valor de fluxo | FA at P1 = 6 bar and pressure drop $\Delta p = 0.2$ bar |



Nota

If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar.
Outras indicações a pedido.

Descrição

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

Artigo

| Descrição | Rosca | Fluxo (L/min) | A (mm) | B | C (mm) | D (mm) | DN | Tamanho |
|----------------|-------|---------------|--------|---------|--------|--------|----|---------|
| K- 07 25 10 46 | G 1/8 | 310 | 40,0 | 97,3 mm | 12,3 | 85,0 | 5 | 0 |

Acessório para

| | |
|------------------------------|--|
| K-AUTOMAT ABLASSVENTIL | Automatic drain valve |
| K-KOPPELPAKET MEHR | Coupling packet |
| K-ERSATZBEHAELTER MULTI MINI | Spare tank »multifix-mini« & »standard-mini« |