


K-VT 2 ABGAENGE G

Manifolds

HANSA FLEX

Características

| | |
|-----------------------|------------------------|
| Pressão de entrada | 0 - 9 bar |
| Temperatura do fluido | max. 70 °C |
| Temperatura ambiente | Max. 70 °C |
| Material de vedação | NBR |
| Carcaça | Die-cast aluminium |
| Outras indicações | User manual on request |



Artigo

| Descrição | Rosca | A (mm) | B | C (mm) | D (mm) | Tamanho |
|----------------|-------|-----------|---------|-----------|-----------|---------|
| K- 07 25 12 19 | G 1/4 | 35,0 | 44,0 mm | 22,0 | 22,0 | 200 |
| K- 07 25 12 20 | G 3/8 | 35,0 | 44,0 mm | 22,0 | 22,0 | 200 |
| K- 07 25 12 21 | G 3/8 | 42,0 | 52,0 mm | 26,0 | 26,0 | 300 |
| K- 07 25 12 22 | G 1/2 | 42,0 | 52,0 mm | 26,0 | 26,0 | 300 |
| K- 07 25 12 23 | G 3/4 | 60,0 | 76,0 mm | 38,0 | 38,0 | 600 |
| K- 07 25 12 24 | G 1 | 60,0 | 76,0 mm | 38,0 | 38,0 | 600 |

Acessórios

| | |
|-----------------------|-----------------|
| K-VERBINDUNGSELEMENTE | Connecting sets |
| K-WANDHALTER | Wall bracket |