K-ENDVERTEILERDOSEN

End porting box without through-hole thread, PN 15

Características

Pressão operacional	Max. 15 bar
Torque Fixação	4 Nm
Torque Rosca MS	12 Nm
Faixa de temperatura	-10 °C to +50 °C
Carcaça	Glass fibre-reinforced plastic
Rosca	Brass



Nota

Outras indicações a pedido.

Descrição

1, 2 or 3-way porting boxes made of high-strength glass fibre-reinforced plastic for a wide range of applications. Available with up to 3 couplings and 2 inlet thread sizes. Optional through-hole thread at the bottom to facilitate the passage of the medium. All porting boxes have a robust, brass threaded insert for high tightening torques, TÜV certified. Suitable for almost any pneumatic application.

Artigo

Descrição	Entrada da rosca	Rosca de conexão
K- 07 40 48 12	Rosca 1/2"	1 x G 1/2
K- 07 40 48 13	Rosca 1/2"	2 x G 1/2
K- 07 40 48 14	Rosca 1/2"	3 x G 1/2
K- 07 40 48 15	Rosca 3/4"	1 x G 1/2
K- 07 40 48 16	Rosca 3/4"	2 x G 1/2
K- 07 40 48 17	Rosca 3/4"	3 x G 1/2

Apesar de uma verificação cuidadosa, não podemos excluir a possibilidade de erros e não assumimos qualquer responsabilidade pelos dados aqui contidos.