

K-LKM S NW10 SCHL TUE

Safety couplings DN 10 mit Schlauchtülle

Características

Pressão operacional	Max. 16 bar
Fluxo de ar	4.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura do fluido	-20 °C to +100 °C
Material	Aço / Latão zincado
Mola	Stainless-steel
Material de vedação	NBR



Nota

Outras indicações a pedido.

Descrição

High-quality, robust and durable, one-hand quick disconnect safety couplings, with very high flow rate and only a small pressure drop. The coupling is released fully automatically in two steps. Air is relieved from the coupling before it is completely disconnected, to minimise the risk of injury to the operator from hose ends flying around. The plug is only disconnected from the coupling if the residual pressure has dropped below 0.3 bar. The dreaded "whiplash effect" is thus avoided and the risk of injury virtually eliminated. This safety version conforms to ISO-Standard DIN EN ISO 4414. Suitable for all applications with an above-average air consumption and characterised by extreme conditions.

Artigo

Descrição	Conexão	Comprimento (mm)	SW (mm)
K- 07 35 12 98	Stem, I.D. 10	77,0	24
K- 07 35 13 01	Stem, I.D. 13	75,3	24
K- 07 35 13 02	Stem, I.D. 16	75,3	24
K- 07 35 13 03	Stem, I.D. 19	74,3	24

Elementos complementares

K-NIPPEL KUPPL NW10 AG ROBU	Plugs for couplings DN 10, hardened, galvanised steel, robust type, male
K-NIPPEL KUPPL NW10 IG ROBU	Plugs for couplings DN 10, hardened, galvanised steel, robust type, female
K-TUE 1 ST K VZ	Stems for couplings DN 10, hardened, galvanised steel, robust type