

# K-SCHLAUCH KUPPLUNG SET SICH

Hose and coupling kits, with straight hose and DN 7.6 safety coupling

**HANSA FLEX**

## Características

|                       |                  |
|-----------------------|------------------|
| Pressão operacional   | 16 bar           |
| Temperatura do fluido | -20 °C to +60 °C |



## Nota

Outras indicações a pedido.

## Descrição

Couplings: High-grade single-handed quick-release coupling and safety coupling in steel / brass zinc-plated for high flow rates, specially designed for all applications with high mechanical wear. Strong, impact- and vibration-resistant construction for challenging applications. Polyurethane hose Exceedingly flexible, extremely kink-resistant and tolerant of dirt spiral hose with high resilience under tear, tensile and impact loads with a long service life and outstanding ageing qualities. It is also UV resistant and has outstanding abrasion resistance.

## Artigo

| Descrição      | Dimensão da mangueira | Comprimento de trabalho<br>(m) |
|----------------|-----------------------|--------------------------------|
| K- 07 10 05 58 | 12 mm x 8 mm          | 10,0                           |
| K- 07 10 05 59 | 12 mm x 8 mm          | 15,0                           |
| K- 07 10 05 60 | 16 mm x 11 mm         | 10,0                           |
| K- 07 10 05 61 | 16 mm x 11 mm         | 15,0                           |