

K-WV 3/2 LB NAMUR GETAUSCHT

3/2-way spool valves with NAMUR style interface, NC, ports 1 and 3 or 2 and 3 swapped

HANSA FLEX

Características

Fluidos	Air, neutral gases, filtered
Pressão de trabalho	1.5 to 10 bar
Temperatura operacional	-20 °C to +70 °C
Conexão elétrica	Plug connector PG 9
Incluso no escopo de fornecimento	Plug connector PG 9, 1 coding pin, 2 O-rings, 2 fixing screws
Consumo de potência	3 W=/5 VA~
Carcaça	Aluminium, anodised
Válvula	Stainless steel
Material de vedação	NBR



Nota

Outras indicações a pedido.

Descrição

3/2 and 5/2-way spool valves, monostable, with air purging function and pneumatic spring return. With latching manual operator and optional outgoing air restriction.

Two or three-piece service units with excellent flow rates in modern design.
Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

Artigo

Descrição	Tensão	Conexão	DN	Fluxo (L/min)
K- 07 15 00 05	230 V, 50 Hz	G 1/4	7	1250
K- 07 15 00 06	24 V DC	G 1/4	7	1250