

# K-SVKM NW 7,2 DREH MS-NI

Quick disconnect couplings DN 7.2, nickel-plated brass, swivel type

**HANSA FLEX**

## Características

<b>Pressão operacional</b>	0 - 35 bar, maximum static working pressure (non-pulsating)
<b>Fluxo de ar</b>	1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
<b>Temperatura do fluido</b>	0 °C to +70 °C
<b>Carcaça, manga</b>	Nickel-plated brass
<b>Válvula</b>	Brass with a bare metal surface
<b>Mola, anel de trava</b>	Stainless steel 1.4310
<b>Pinos de bloqueio</b>	Stainless steel 1.4034
<b>Material de vedação</b>	NBR



## Nota

Outras indicações a pedido.

## Descrição

Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt. In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins.

## Artigo

Descrição	Conexão	Comprimento (mm)
K- 07 35 07 28	Stem 6 mm, swivel type	74,0
K- 07 35 07 29	Stem 8 mm, swivel type	74,0
K- 07 35 07 30	Stem 9 mm, swivel type	74,0
K- 07 35 07 31	Stem, 10 mm, swivel type	74,0
K- 07 35 07 32	Stem, 13 mm, swivel type	74,0

## Elementos complementares

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass