


K-NIPPEL KUPPL NW7 AG VZ PTFE

Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, male threaded, FPM (PTFE coated) seal

HANSA FLEX

Características

Pressão operacional	Max. 16 bar
Fluxo de ar	2.100 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura do fluido	-20 °C to +100 °C
Material	Aço endurecido e zincado



Nota

Outras indicações a pedido.

Artigo

Descrição	Definição	SW (mm)
K- 07 35 12 88	Plug R 1/8 male	13
K- 07 35 02 49	Plug R 1/4 male	14
K- 07 35 02 50	Plug R 3/8 male	17
K- 07 35 02 51	Plug R 1/2 male	22

é elemento complementar para os seguintes produtos

K-SVKM NW 7,6 AG ST-MS VZ	Quick disconnect couplings DN 7.6, galvanised steel / brass, male
K-SVKM NW 7,6 IG ST	Quick disconnect couplings DN 7.6, galvanised steel / nickel-plated brass, female
K-SVKM NW 7,6 SCHL TUE ST VZ	Quick disconnect couplings DN 7.6, galvanised steel / brass, with hose connector
K-SVKM NW 7,6 STREAM LINE ST	Quick disconnect couplings DN 7.6, galvanised steel / brass, »stream line«
K-LKM S NW7,6 AG	Safety couplings DN 7.6, male
K-LKM S NW7,6 IG	Safety couplings DN 7.6, female
K-LKM S NW7,6 SCHL TUE	Safety couplings DN 7.6, with hose stem
K-LKM S NW7,6 STRAEM LINE	Safety couplings DN 7.6 »stream line«