

K-SVKM NW 7,8 IG H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, female

HANSA FLEX

Características

Pressão operacional	0 - 35 bar
Fluxo de ar	2.100 l/min (at $\Delta p = 0.5$ bar)
Temperatura do fluido	-20 °C to +40 °C
Peça roscada	Nickel-plated brass
Corpo da válvula	Steel, QPQ treated
Manga de desbloqueio	Extremely robust, ergonomic plastic
Válvula, assento	Brass
Fluidos	Only for clean compressed air
Vedações	NBR
Mola, anel de trava, esferas	stain less steel



Nota

Outras indicações a pedido.

Descrição

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

Artigo

Descrição	Conexão	Comprimento (mm)	SW (mm)
K- 07 35 08 50	G 1/4 female	59,0	19
K- 07 35 08 51	G 3/8 female	59,0	19
K- 07 35 08 52	G 1/2 female	62,0	24

Elementos complementares

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass