

K-SVKM NW 7,8 AG VA

Quick disconnect couplings DN 7.8, stainless steel 1.4305, male

HANSA FLEX

Características

| | |
|----------------------------------|---|
| Pressão operacional | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Fluxo de ar | 1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar) |
| Temperatura do fluido | -15 °C to +200 °C |
| Carcaça, manga, corpo da válvula | Stainless steel 1.4305 |
| Mola, anel de trava, esferas | Stainless steel |
| Material de vedação | FKM |



Nota

Outras indicações a pedido.

Descrição

One-hand quick disconnect couplings, one side sealing, made of stainless steel 1.4305. Ideal for: Pneumatic tools, laboratory equipment, chemical applications, instrumentation and control, safety systems, industrial plant engineering, mechanical engineering.

Artigo

| Descrição | Conexão | Comprimento (mm) | SW (mm) |
|----------------|------------|------------------|---------|
| K- 07 35 07 90 | G 1/4 male | 59,5 | 19 |
| K- 07 35 07 91 | G 3/8 male | 57,5 | 19 |
| K- 07 35 07 92 | G 1/2 male | 60,5 | 24 |

Elementos complementares

| | |
|----------------------------|---|
| K-NIPPEL KUPPL NW7 AG VA 1 | Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, male |
| K-NIPPEL KUPPL NW7 IG VA 2 | Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, female |
| K-TUE 7,2 7,8 VA 1 | Stems for couplings DN 7.2 - DN 7.8, stainless steel 1.4305 |