

K-LKM S NW7,8 SCHL TUE

Safety couplings DN 7.8, with hose stem

HANSA FLEX

Características

| | |
|--------------------------|---|
| Pressão operacional | máx. 20 bar |
| Fluxo de ar | 1.400 l/min (at 6 bar and $\Delta p = 0.5$ bar) |
| Temperatura do fluido | -20 °C to +100 °C |
| Conexão corpo da válvula | Nickel-plated brass |
| Mola, esferas | Stainless-steel |
| Luva deslizante | Anodised aluminium |
| Manga de desbloqueio | Hardened and nickel-plated steel |
| Material de vedação | NBR |



Nota

Outras indicações a pedido.

Descrição

Safety air relief couplings for gaseous media. Combination of a sliding valve and a quick disconnect coupling! Connection is pressureless. Only a low spring force has to be overcome. Pressure only builds up when the blue sleeve is pushed forward. It is impossible to disconnect the hose either intentionally or inadvertently in this position. When the sliding sleeve is moved back into its home position, the air is relieved from the hose and the coupling can be disconnected.

Artigo

| Descrição | Conexão | Comprimento (mm) |
|----------------|---------------|------------------|
| K- 07 35 08 88 | Stem, I.D. 6 | 86,0 |
| K- 07 35 12 96 | Stem, I.D. 8 | 86,0 |
| K- 07 35 08 89 | Stem, I.D. 9 | 86,0 |
| K- 07 35 12 97 | Stem, I.D. 10 | 86,0 |
| K- 07 35 08 90 | Stem, I.D. 13 | 86,0 |

Elementos complementares

| | |
|-------------------------------|--|
| K-NIPP KUPPL NW7 SCHL MS NI K | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring |
| K-NIPPEL KUPPL NW7 AG MS NI | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male |
| K-NIPPEL KUPPL NW7 IG MS NI | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female |
| K-NIPPEL KUPPL NW7 SCHL MS NI | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose |
| K-TUE 5 MS NI | Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass |