

# K-SVKM NW 5 SCHL UEB MS BL

Quick disconnect couplings DN 5, brass with a bare metal surface, with swivel nut and kink protector spring

**HANSA FLEX**

## Características

Pressão operacional	0 - 35 bar, maximum static working pressure (non-pulsating)
Fluxo de ar	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura do fluido	-20 °C to +100 °C
Carcaça, manga, corpo da válvula	Brass
Mola, anel de trava, esferas	Stainless steel
Material de vedação	NBR



## Nota

Outras indicações a pedido.

## Descrição

One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. Ideal for: Pneumatic tools, pneumatic applications, medical equipment, instrumentation and control, laboratory, chemical applications, analysis, metering techniques.

## Artigo

Descrição	Conexão	Modelo	Comprimento (mm)	SW (mm)
K- 07 35 06 48	Hose connection 6 x 4	rígido	120,0	14
K- 07 35 06 49	Hose connection 8 x 6	rígido	132,0	14
K- 07 35 06 50	Hose connection 6 x 4	giratório 360°	134,0	14
K- 07 35 06 51	Hose connection 8 x 6	giratório 360°	145,0	14