


# K-ELEKTRISCHE ANSCHLUESSE

Electrical connection (multi-pole, 25-pin, IP 65)

**HANSA FLEX**

## Características

|                                    |   |
|------------------------------------|---|
| <b>Fluidos</b>                     | Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. |
| <b>Pressão de trabalho</b>         | Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)                      |
| <b>Pressão de controle</b>         | 3 - 7 bar   |
| <b>Faixa de temperatura</b>        | -10 °C to +60 °C  |
| <b>Fluxo</b>                       | 200 NI/min (Ø 4), 500 NI/min (Ø 6), 800 NI/min (Ø 8)  |
| <b>Número de acionamentos</b>      | Max. 16 (e.g. 16 spring return valves)  |
| <b>Acionamento auxiliar manual</b> | Latching (bistable), Monostable (non-latching) version also available on request                    |
| <b>Consumo de potência</b>         | 0.6 W per pilot   |
| <b>Tipo de proteção</b>            | IP 65   |



## Nota

Outras indicações a pedido.

## Descrição

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

## Informações adicionais

Important: The scope of supply does not include a connector. Please order separately.

## Artigo

| Descrição      | Definição                                 |
|----------------|---|
| K- 07 15 22 45 | IP 67 connector, 25-pin, with 1 m cable   |
| K- 07 15 22 46 | IP 67 connector, 25-pin, with 2.5 m cable |
| K- 07 15 22 47 | IP 67 connector, 25-pin, with 5 m cable   |