K-WV 3/2 5/2 NAMUR LB FR

3/2- and 5/2-way spool valves with NAMUR style interface and combined spring return

Características

Fluidos	Air, neutral gases (filtered)
Pressão de trabalho	1.5 to 10 bar (552.11 and 552.12); 2.5 to 10 bar (552.21 and 552.22)
Temperatura operacional	-20 °C to +50 °C
Conexão 1 - 3	G 1/4 (Port 1), G 1/4 (Port 3 and 5)
Conexão 1/3 + 5	G 1/4 (Port 1), G 1/4 (Port 3 and 5)
Conexão elétrica	Plug connector PG 9
incluso no escopo de fornecimento	Plug connector PG 9, conversion plate, screws and seal
Consumo de potência	3 W=/5 VA~
Carcaça	Anodised aluminium
Válvula	Stainless steel
Material de vedação	NBR



Nota

Outras indicações a pedido.

Descrição

Pilot-operated 3/2- and 5/2-way spool valves with threaded ports and a NAMUR style interface with air purging function. By adding the conversion plate supplied with each valve, the device can be adapted to 3/2-way function.
Filter regulators are also available with bowl guard or metal bowl. Filter regulators are also available in lockable version. Please ask for more information.

Artigo

Descrição	Tensão	Port 1	Conexão 3 + 5	DN	Fluxo (L/min)
K- 07 15 00 15	230 V, 50 Hz	G 1/4	G 1/4	7	1250
K- 07 15 00 16	24 V DC	G 1/4	G 1/4	7	1250

Apesar de uma verificação cuidadosa, não podemos excluir a possibilidade de erros e não assumimos qualquer responsabilidade pelos dados aqui contidos.