
K-VSTO POM

Plugs



Características	
Pressão de trabalho	0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)
Temperatura operacional	-20 °C to +70 °C in air; +1 °C to +70 °C in water
Material	Poliacetal (POM)
Material de vedação	NBR





Nota

Outras indicações a pedido.

Descrição

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Artigo				
Descrição	Cor	L1 (mm)	Bocal _(mm)	
K- 07 40 29 11	vermelho	28,0	4	
K- 07 40 29 12	vermelho	28,0	5	
K- 07 40 29 13	vermelho	30,0	6	
K- 07 40 29 14	vermelho	31,0	8	
K- 07 40 29 15	vermelho	36,5	10	
K- 07 40 29 16	vermelho	38,5	12	
K- 07 40 29 17	preto	45,0	15	
K- 07 40 29 18	preto	41,5	18	
K- 07 40 29 19	preto	45,0	22	
K- 07 40 29 20	preto	56,0	28	