

# K-VSTO POM

## Plugs

### Características

<b>Pressão de trabalho</b>	0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)
<b>Temperatura operacional</b>	-20 °C to +70 °C in air; +1 °C to +70 °C in water
<b>Material</b>	Poliacetil (POM)
<b>Material de vedação</b>	NBR



### Nota

Outras indicações a pedido.

### Descrição

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

### Artigo

Descrição	Cor	L1 (mm)	Bocal (mm)
K- 07 40 29 11	vermelho	28,0	4
K- 07 40 29 12	vermelho	28,0	5
K- 07 40 29 13	vermelho	30,0	6
K- 07 40 29 14	vermelho	31,0	8
K- 07 40 29 15	vermelho	36,5	10
K- 07 40 29 16	vermelho	38,5	12
K- 07 40 29 17	preto	45,0	15
K- 07 40 29 18	preto	41,5	18
K- 07 40 29 19	preto	45,0	22
K- 07 40 29 20	preto	56,0	28