


K-LKM S NW7,4 DREH AG VA

Safety couplings DN 7.4, stainless steel 1.4404, male, swivel type

HANSA FLEX

Características

Pressão operacional	máx. 10 bar
Fluxo de ar	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Temperatura do fluido	-20 °C to +150 °C
Carcaça	Stainless steel 1.4404
Rosca	Stainless steel 1.4404
Peças interiores	Stainless steel 1.4404
Botão, válvula	Stainless steel 1.4404
Material de vedação	FKM



Nota

Not suitable for hitting / pulsating tools.
Outras indicações a pedido.

Descrição

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

Informações adicionais

Not suitable for hitting / pulsating tools.

Artigo

Descrição	Conexão	Comprimento (mm)	SW (mm)
K- 07 35 12 76	G 1/4 male	70,5	21
K- 07 35 12 77	G 3/8 male	70,0	21
K- 07 35 12 78	G 1/2 male	72,5	25