


# K-STECKVERBINDU 1

Straight push-in connector

**HANSA FLEX**

## Características

|                         |                  |
|-------------------------|------------------|
| Pressão de trabalho     | Max. 16 bar      |
| Temperatura operacional | -20 °C to +80 °C |
| Material                | Latão niquelado  |
| Anel de pressão         | Hostaform        |
| Anel tensor             | Stainless steel  |



## Nota

Outras indicações a pedido.

## Descrição

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Artigo

| Descrição      | Rosca      | para Ø externo da mangueira | L1<br>(mm) |
|----------------|------------|-----------------------------|------------|
| K- 07 40 25 18 | M 8 x 0.75 | 3 mm                        | 18,4       |
| K- 07 40 25 19 | M 11 x 1   | 4 mm                        | 30,6       |
| K- 07 40 25 20 | M 14 x 1   | 5 mm                        | 33,5       |
| K- 07 40 25 21 | M 13 x 1   | 6 mm                        | 33,0       |
| K- 07 40 25 22 | M 15 x 1   | 8 mm                        | 35,7       |
| K- 07 40 25 23 | M 17 x 1   | 10 mm                       | 39,2       |
| K- 07 40 25 24 | M 20 x 1   | 12 mm                       | 39,7       |
| K- 07 40 25 25 | M 24 x 1   | 14 mm                       | 45,9       |