


K-STECKVERSCHR AGR-K SK BESCH

Male connectors, conical male thread, coated with outer hex

HANSA FLEX

Características

| | |
|-------------------------|---------------------|
| Pressão de trabalho | Max. 16 bar |
| Temperatura operacional | -20 °C to +150 °C |
| Material | Latão niquelado |
| Anel de pressão | Nickel-plated brass |
| Anel tensor | Stainless steel |



Nota

Outras indicações a pedido.

Descrição

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring. All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

Artigo

| Descrição | Rosca | para Ø externo da mangueira | L1 (mm) | SW |
|----------------|-------|-----------------------------|---------|-------|
| K- 07 40 27 26 | R 1/8 | 4 mm | 22,5 | 10 mm |
| K- 07 40 27 27 | R 1/8 | 6 mm | 24,5 | 11 mm |
| K- 07 40 27 28 | R 1/8 | 8 mm | 27,5 | 13 mm |
| K- 07 40 47 62 | R 1/4 | 4 mm | 22,5 | 14 mm |
| K- 07 40 27 24 | R 1/4 | 6 mm | 24,5 | 14 mm |
| K- 07 40 27 25 | R 1/4 | 8 mm | 27,5 | 13 mm |
| K- 07 40 27 23 | R 1/4 | 10 mm | 32,5 | 16 mm |
| K- 07 40 47 61 | R 1/4 | 12 mm | 32,5 | 17 mm |
| K- 07 40 27 30 | R 3/8 | 8 mm | 28,0 | 17 mm |
| K- 07 40 27 29 | R 3/8 | 10 mm | 32,5 | 17 mm |
| K- 07 40 47 63 | R 3/8 | 12 mm | 30,5 | 17 mm |
| K- 07 40 47 60 | R 1/2 | 12 mm | 33,0 | 22 mm |