K-WERKST-SCHLAUCH SOFT

Workshop hose soft

Características

Camada interna	Soft-PVC, black
Reforço	Trançado de poliéster
Camada externa	PVC-flexível, azul
Temperatura	-20 °C to +60 °C
Comprimento do rolo	50 m



Nota

Outras indicações a pedido.

Descrição

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

Artigo

Descrição	Ø interno da mangueira (mm)	Ø externo da mangueira (mm)	Max. working pressure resistance at 23°C (bar)	Raio de curvatura mín. (mm)
K- 07 10 10 33	6,3	11,0	15	23
K- 07 10 10 34	8,0	13,0	15	28
K- 07 10 10 35	9,0	14,5	15	32
K- 07 10 10 36	10,0	15,5	15	35
K- 07 10 10 37	12,7	19,0	15	45
K- 07 10 10 38	16,0	23,0	15	56
K- 07 10 10 39	19,0	26,5	15	67
K- 07 10 10 40	25,0	33,5	15	88

Apesar de uma verificação cuidadosa, não podemos excluir a possibilidade de erros e não assumimos qualquer responsabilidade pelos dados aqui contidos.