

K-FI MIKRO PC-BEHÄLTER SCHÜBESCHUTZ VARIOBLOCK

Micro-filters with polycarbonate bowl and bowl guard

HANSA FLEX

Características

Pressão de entrada	Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Temperatura do fluido	max. 50 °C
Temperatura ambiente	Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)
Unidade filtrante	0,01 µm
Qualidade do ar ISO 85731	Class 1 dirt, class 1 oil
Grau de eficiência	99.999 %
Medição do valor de fluxo	At P1 = 7 bar and pressure drop $\Delta p = 0,1$ bar



Nota

Outras indicações a pedido.

Descrição

Borosilicate filter for all applications where compliance with strict compressed air purity requirements is vital. As the second stage downstream of the standard filter, the micro-filter removes 99.999 % of even the finest remaining particles from water, oil and dirt with practically zero residues (filter rating: 0.01 µm).

Instruções de encomenda

Micro-filters are also available with bowl guard or metal bowl.

Artigo

Descrição	Rosca	Fluxo (L/min)	A (mm)	B	C (mm)
K- 07 25 22 96	G 1/4	370	48,0	155,0 mm	22,0
K- 07 25 22 95	G 3/8	420	48,0	155,0 mm	22,0
K- 07 25 22 94	G 1/2	1000	70,0	202,0 mm	26,0
K- 07 25 22 93	G 3/4	1100	70,0	202,0 mm	26,0
K- 07 25 22 92	G 1	1100	124,0	202,0 mm	26,0