

K-DURCHGANGSVERTEILERDOSE

Through porting box with through-hole thread, PN 15

HANSA FLEX

Características

| | |
|----------------------|--------------------------------|
| Pressão operacional | Max. 15 bar |
| Torque Fixação | 4 Nm |
| Torque Rosca MS | 12 Nm |
| Faixa de temperatura | -10 °C to +50 °C |
| Carcaça | Glass fibre-reinforced plastic |
| Rosca | Brass |



Nota

Outras indicações a pedido.

Descrição

1, 2 or 3-way porting boxes made of high-strength glass fibre-reinforced plastic for a wide range of applications. Available with up to 3 couplings and 2 inlet thread sizes. Optional through-hole thread at the bottom to facilitate the passage of the medium. All porting boxes have a robust, brass threaded insert for high tightening torques, TÜV certified. Suitable for almost any pneumatic application.

Artigo

| Descrição | Entrada da rosca | Rosca de passagem | Rosca de conexão |
|----------------|------------------|-------------------|------------------|
| K- 07 40 48 04 | Rosca 1/2" | G 1/2 | 1 x G 1/2 |
| K- 07 40 48 05 | Rosca 1/2" | G 1/2 | 2 x G 1/2 |
| K- 07 40 48 06 | Rosca 1/2" | G 1/2 | 3 x G 1/2 |
| K- 07 40 48 07 | Rosca 3/4" | G 3/4 | 1 x G 1/2 |
| K- 07 40 48 08 | Rosca 3/4" | G 3/4 | 2 x G 1/2 |
| K- 07 40 48 09 | Rosca 3/4" | G 3/4 | 3 x G 1/2 |