


K-LKM S NW7,6 STRAEM LINE

Safety couplings DN 7.6 »stream line«

HANSA FLEX

Características

| | |
|-----------------------|---|
| Pressão operacional | Max. 16 bar |
| Fluxo de ar | 2.250 l/min (at 6 bar and $\Delta p = 0.5$ bar) |
| Temperatura do fluido | -20 °C to +100 °C |
| Material | Aço / Latão zincado |
| Mola | Stainless-steel |
| Material de vedação | NBR |



Nota

Outras indicações a pedido.

Descrição

High-quality, robust and durable, one-hand quick disconnect safety couplings, with very high flow rates and only a small pressure drop. The coupling is released fully automatically in two steps. Air is relieved from the coupling before it is completely disconnected, to minimise the risk of injury to the operator from hose ends flying around. The plug is only disconnected from the coupling if the residual pressure has dropped below 0.3 bar. The dreaded "whiplash effect" is thus avoided and the risk of injury virtually eliminated. This safety version conforms to ISO-Standard DIN EN ISO 4414.

Artigo

| Descrição | para mangueira | Comprimento (mm) | SW1 (mm) | SW2 (mm) |
|----------------|----------------|------------------|----------|----------|
| K- 07 35 13 08 | 10 x 6,5 | 64,1 | 16 | 20 |
| K- 07 35 13 10 | 12 x 8 | 68,1 | 19 | 20 |
| K- 07 35 13 12 | 13,5 x 9,5 | 68,2 | 21 | 20 |
| K- 07 35 13 15 | 16 x 11 | 68,1 | 24 | 24 |

Elementos complementares

| | |
|-------------------------------|---|
| K-NIPPEL KUPPL NW7 AG VZ PTFE | Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, male threaded, FPM (PTFE coated) seal |
| K-NIPPEL KUPPL NW7 IG VZ 1 | Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, female |
| K-NIPPEL KUPPL STREAM LINE | Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel »stream line« |
| K-TUE 7,2 7,8 ST VZ 2 | Stems for couplings DN 7.2 - DN 7.8, hardened and galvanised steel |