

K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling

HANSA FLEX

Características

| | |
|-------------------------|--|
| Aplicação | Air, gases, oils, greases, fuels, organic and inorganic substances |
| Temperatura operacional | -40 °C to +100 °C |
| Tipo de conexão | connection nipples and coupling NW 7,2 |



Nota

Outras indicações a pedido.

Descrição

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Artigo

| Descrição | Ø interno da mangueira (mm) | Ø externo da mangueira (mm) | Ø externo da espiral (mm) | Torções | Max. working pressure resistance at 23°C (bar) | Comprimento de trabalho máx. (m) |
|----------------|-----------------------------|-----------------------------|---------------------------|---------|--|----------------------------------|
| K- 07 10 12 95 | 6,3 | 7,9 | 75 | 15 | 13 | 2,5 |
| K- 07 10 12 96 | 6,3 | 7,9 | 75 | 30 | 13 | 5,0 |
| K- 07 10 12 97 | 6,3 | 7,9 | 75 | 45 | 13 | 7,5 |
| K- 07 10 12 65 | 7,9 | 9,5 | 115 | 10 | 12 | 2,5 |
| K- 07 10 12 66 | 7,9 | 9,5 | 115 | 20 | 12 | 5,0 |
| K- 07 10 12 67 | 7,9 | 9,5 | 115 | 30 | 12 | 7,5 |
| K- 07 10 12 68 | 9,5 | 11,8 | 140 | 8 | 11 | 2,5 |
| K- 07 10 12 69 | 9,5 | 11,8 | 140 | 15 | 11 | 5,0 |
| K- 07 10 12 70 | 9,5 | 11,8 | 140 | 23 | 11 | 7,5 |

Acessórios

| | |
|--------------------------|-------------------------------------|
| K-DREHBARE VERSCHR KNICK | Swivel adapters with kink protector |
| K-STARRE VERSCHRAUBUNG | Rigid adapters with kink protector |