

K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling

HANSA FLEX

Características

Aplicação	Air, gases, oils, greases, fuels, organic and inorganic substances
Temperatura operacional	-40 °C to +100 °C
Tipo de conexão	connection nipples and coupling NW 7,2



Nota

Outras indicações a pedido.

Descrição

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Artigo

Descrição	Ø interno da mangueira (mm)	Ø externo da mangueira (mm)	Ø externo da espiral (mm)	Torções	Max. working pressure resistance at 23°C (bar)	Comprimento de trabalho máx. (m)
K- 07 10 12 95	6,3	7,9	75	15	13	2,5
K- 07 10 12 96	6,3	7,9	75	30	13	5,0
K- 07 10 12 97	6,3	7,9	75	45	13	7,5
K- 07 10 12 65	7,9	9,5	115	10	12	2,5
K- 07 10 12 66	7,9	9,5	115	20	12	5,0
K- 07 10 12 67	7,9	9,5	115	30	12	7,5
K- 07 10 12 68	9,5	11,8	140	8	11	2,5
K- 07 10 12 69	9,5	11,8	140	15	11	5,0
K- 07 10 12 70	9,5	11,8	140	23	11	7,5

Acessórios

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector