

# K-SPIR SCHL KUPPL SET LKM NW 7,4

Spiral hose and coupling kit with pushbutton-type safety coupling (DN 7.4) and push-in plug, galvanised steel

**HANSA FLEX**

## Características

|                         |  |
|-------------------------|--|
| Tipo de conexão         | with pushbutton safety coupling NW 7,4 steel nipple galvanised |
| Temperatura operacional | -40 °C to +74 °C   |



## Nota

Outras indicações a pedido.

## Descrição

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Não adequada para ferramentas com batidas ou pulsantes!

## Artigo

| Descrição      | Ø interno da mangueira (mm) | Ø externo da mangueira (mm) | Torção externa Ø (mm) | Max. working pressure resistance at 23°C (bar) | Comprimento de trabalho máx. (m) |
|----------------|-----------------------------|-----------------------------|-----------------------|--|----------------------------------|
| K- 07 10 12 71 | 5,0                         | 8,0                         | 40                    | 10   | 3,0                              |
| K- 07 10 12 73 | 5,0                         | 8,0                         | 40                    | 10   | 6,0                              |
| K- 07 10 12 75 | 5,0                         | 8,0                         | 40                    | 10   | 7,5                              |
| K- 07 10 12 80 | 6,3                         | 9,5                         | 60                    | 10   | 3,0                              |
| K- 07 10 12 82 | 6,3                         | 9,5                         | 60                    | 10   | 6,0                              |
| K- 07 10 12 84 | 6,3                         | 9,5                         | 60                    | 10   | 7,5                              |
| K- 07 10 12 78 | 6,3                         | 9,5                         | 60                    | 10   | 10,0                             |
| K- 07 10 12 89 | 8,0                         | 12,0                        | 80                    | 9  | 3,0                              |
| K- 07 10 12 91 | 8,0                         | 12,0                        | 80                    | 9  | 6,0                              |
| K- 07 10 12 93 | 8,0                         | 12,0                        | 80                    | 9  | 7,5                              |
| K- 07 10 12 87 | 8,0                         | 12,0                        | 80                    | 9  | 10,0                             |

## Acessórios

|                          |                 |
|--------------------------|-----------------|
| K-DREHBARE VERSCHRAUBUNG | Swivel adapters |
|--------------------------|-----------------|