K-STOSSDAEMPFER RB

Shock absorber RB

Características

Série	RB
Outras indicações	high power density through hydraulic function principle results in min.. size Impact speed up to max. 5 m / sec. Annular surface at the front side can be used as a mechanical stop



Descrição

Shock absorber, series RB, high power density from hydraulic design principle results in min. dimensions, impact speed up to max. 5 m/sec., the annulus on the end can be used as a mechanical stop, basic version, thread M 8 x 1, stroke 6 mm

Artigo

Descrição	Curso (mm)	Modelo	Definição	Rosca
K- 07 55 02 24	5	Modelo básico	Shock absorber	M 8 x 1
K- 07 55 02 25	6	Modelo básico	Shock absorber	M 8 x 1
K- 07 55 02 27	6	Modelo básico	Shock absorber	M 10 x 1
K- 07 55 02 28	7	Modelo básico	Shock absorber	M 10 x 1
K- 07 55 02 30	11	Modelo básico	Shock absorber	M 14 x 1,5
K- 07 55 02 31	12	Modelo básico	Shock absorber	M 14 x 1,5
K- 07 55 02 33	15	Modelo básico	Shock absorber	M 20 x 1,5
K- 07 55 02 35	25	Modelo básico	Shock absorber	M 27 x 1,5

Apesar de uma verificação cuidadosa, não podemos excluir a possibilidade de erros e não assumimos qualquer responsabilidade pelos dados aqui contidos.