
K-W90 STUECK IG IG MS NI

90° elbows, female/female



| Características | | | | |
|-------------------------|------------------------------|--|--|--|
| Pressão operacional | 60 bar | | | |
| Temperatura operacional | Max. 150 °C | | | |
| Rosca interna | Parallel to DIN EN ISO 228-1 | | | |
| Material | Latão niquelado | | | |





Nota

Outras indicações a pedido.

| Artigo | | | | | |
|----------------|-------|------------|------------|-------|--|
| Descrição | Rosca | L1 (mm) | L2 (mm) | SW | |
| K- 07 40 48 90 | M 5 | 11,0 | 11,0 | 9 mm | |
| K- 07 40 10 86 | G 1/8 | 21,0 | 21,0 | 10 mm | |
| K- 07 40 10 87 | G 1/4 | 25,5 | 25,5 | 13 mm | |
| K- 07 40 10 88 | G 3/8 | 28,0 | 28,0 | 17 mm | |
| K- 07 40 10 89 | G 1/2 | 33,5 | 33,5 | 21 mm | |
| K- 07 40 10 96 | G 3/4 | 36,5 | 36,5 | 25 mm | |
| K- 07 40 10 97 | G 1 | 45,0 | 45,0 | 30 mm | |