

# LKM HR ST DK

Engate-rápido de encaixe (ar) - parte fêmea com retentor

**HANSA FLEX**

## Características

<b>Tipo</b>	Engate-rápido fêmea
<b>Conexão 1</b>	Rosca externa BSP cilíndrica
<b>Conexão 2</b>	
<b>Pressão operacional</b>	máx. 12 bar
<b>Fluxo de ar</b>	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
<b>Temperatura do fluido</b>	-20 °C to +70 °C
<b>Carcaça</b>	Aluminium, anodised
<b>Rosca</b>	Nickel-plated brass
<b>Peças interiores</b>	Stainless steel
<b>Botão, válvula</b>	Hardened, galvanised steel
<b>Material de vedação</b>	NBR



## Nota

Not suitable for hitting / pulsating tools.  
Outras indicações a pedido.

## Descrição

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

## Artigo

Descrição	Rosca de conexão	Conexão	Comprimento (mm)	SW (mm)
LKM 06 HR ST DK	Rosca 1/4" -19	G 1/4 male	70,5	21
LKM 10 HR ST DK	Rosca 3/8" -19	G 3/8 male	70,0	21
LKM 13 HR ST DK	Rosca 1/2" -14	G 1/2 male	72,5	25