

LKM IR ST DK

Engate-rápido de encaixe (ar) - parte fêmea com retentor

HANSA FLEX

Características

Tipo	Engate-rápido fêmea
Conexão 1	Rosca interna BSP cilíndrica
Conexão 2	
Pressão operacional	máx. 12 bar
Fluxo de ar	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Temperatura do fluido	-20 °C to +70 °C
Carcaça	Aluminium, anodised
Rosca	Nickel-plated brass
Peças interiores	Stainless steel
Botão, válvula	Hardened, galvanised steel
Material de vedação	NBR



Nota

Not suitable for hitting / pulsating tools.
Outras indicações a pedido.

Descrição

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

Artigo

Descrição	Rosca de conexão	Conexão	Comprimento (mm)	SW (mm)
LKM 06 IR ST DK	Rosca 1/4" -19	G 1/4 female	71,5	21
LKM 10 IR ST DK	Rosca 3/8" -19	G 3/8 female	75,5	21
LKM 13 IR ST DK	Rosca 1/2" -14	G 1/2 female	77,5	24