

### Caracteristici

|                             |                       |
|-----------------------------|-----------------------|
| <b>Racord 1</b>             | Filete BSP de piuliță |
| <b>Tip constructiv</b>      | Piuliță olandeză      |
| <b>Standard</b>             | ISO 8434-6            |
| <b>Material</b>             | Oțel                  |
| <b>Protecția suprafeței</b> | acoperire galvanică   |



### Articol

| Denumire  | G1           | L1<br>(mm) | S1 |
|-----------|--------------|------------|----|
| UEM AB 02 | G 1/8" -28   | 15,0       | 14 |
| UEM AB 04 | G 1/4" -19   | 15,0       | 17 |
| UEM AB 06 | G 3/8" -19   | 18,0       | 22 |
| UEM AB 08 | G 1/2" -14   | 20,0       | 27 |
| UEM AB 10 | G 5/8" -14   | 23,0       | 27 |
| UEM AB 12 | G 3/4" -14   | 23,0       | 32 |
| UEM AB 16 | G 1" -11     | 26,0       | 41 |
| UEM AB 20 | G 1.1/4" -11 | 28,0       | 50 |
| UEM AB 24 | G 1.1/2" -11 | 32,5       | 60 |

SW , S1, S2 = deschiderea cheii