

Caracteristici

| | |
|----------------------|------------------------|
| Racord 1 | Fișă WEO |
| Formă de etanșare 1 | Ștuț etanșat cu inel O |
| Material | Oțel |
| Protecția suprafeței | acoperire galvanică |



Articol

| Denumire | Dimensiunea constructivă | Presiune de lucru bar | Ø D1 (mm) | Ø D2 (mm) | L1 (mm) | L2 (mm) |
|-------------|--------------------------|-----------------------|--------------|--------------|------------|------------|
| WEO VS 10 S | 1/4" | PN 350 | 10 | 12,0 | 43,0 | 19,0 |
| WEO VS 13 S | 3/8" | PN 350 | 13 | 16,0 | 50,0 | 22,0 |
| WEO VS 16 S | 1/2" | PN 350 | 16 | 19,0 | 50,0 | 22,0 |
| WEO VS 23 S | 3/4" | PN 350 | 23 | 25,0 | 59,0 | 31,0 |
| WEO VS 30 S | 1" | PN 250 | 30 | 33,0 | 75,0 | 38,5 |

Piese de schimb

| | |
|------------------|-------------------------|
| WEO S DEMORING | Inel de demontare WEO |
| WEO S M ANSCHLAG | Limitator de montaj WEO |