

2 OK VC

Clemă cu 2 urechi

HANSA FLEX

Caracteristici

Domeniul de utilizare	Dispozitive de fixare furtun în domeniul presiunii joase și medii.
Material	Oțel
Protecția suprafeței	crom zincat lucios



Articol

Denumire	Domeniul de strângere (mm)	Lățime bandă (mm)
2 OK 3-5 VC	3,0 - 5,0	5,0
2 OK 3.1-4.1 VC	3,1 - 4,1	3,5
2 OK 3.5-4.5 VC	3,5 - 4,5	3,5
2 OK 5-7 VC	5,0 - 7,0	6,0
2 OK 7-9 VC	7,0 - 9,0	7,0
2 OK 8-11 VC	8,0 - 11,0	7,0
2 OK 9-11 VC	9,0 - 11,0	7,0
2 OK 11-13 VC	11,0 - 13,0	7,0
2 OK 13-15 VC	13,0 - 15,0	7,5
2 OK 15-17 VC	15,0 - 17,0	8,0
2 OK 15-18 VC	15,0 - 18,0	8,0
2 OK 16-19 VC	16,0 - 19,0	8,0
2 OK 17-20 VC	17,0 - 20,0	8,5
2 OK 19-22 VC	19,0 - 22,0	9,0
2 OK 20-23 VC	20,0 - 23,0	9,0
2 OK 22-25 VC	22,0 - 25,0	10,0
2 OK 23-25 VC	23,0 - 25,0	10,0
2 OK 23-27 VC	23,0 - 27,0	10,0
2 OK 25-28 VC	25,0 - 28,0	10,0
2 OK 27-31 VC	27,0 - 31,0	10,0
2 OK 28-31 VC	28,0 - 31,0	10,0
2 OK 31-34 VC	31,0 - 34,0	10,0
2 OK 34-37 VC	34,0 - 37,0	10,0
2 OK 37-40 VC	37,0 - 40,0	10,0
2 OK 40-43 VC	40,0 - 43,0	10,0
2 OK 43-46 VC	43,0 - 46,0	10,0

Variante produs

2 OK	Clemă cu 2 urechi, acoperire galvanică
2 OK VA	Clemă cu 2 urechi, oțel inoxidabil