

## Caracteristici

Tip constructiv	Bride cu dantură melcată
Tip constructiv - element suplimentar	Șurub cu cap hexagonal cu fantă
Standard	DIN 3017
Material	Oțel
Protecția suprafeței	zincat



## Articol

Denumire	Domeniu de strângere (mm)	Lățime bandă (mm)
ASK 08-12	8 - 12	9,0
ASK 10-16	10 - 16	9,0
ASK 12-20	12 - 20	9,0
ASK 16-25	16 - 25	12,0
ASK 20-32	20 - 32	12,0
ASK 25-40	25 - 40	12,0
ASK 35-50	35 - 50	12,0
ASK 40-60	40 - 60	12,0
ASK 50-70	50 - 70	12,0
ASK 60-80	60 - 80	12,0
ASK 70-90	70 - 90	12,0
ASK 80-100	80 - 100	12,0
ASK 90-110	90 - 110	12,0
ASK 100-120	100 - 120	12,0
ASK 110-130	110 - 130	12,0
ASK 120-140	120 - 140	12,0
ASK 130-150	130 - 150	12,0
ASK 140-160	140 - 160	12,0
ASK 150-170	150 - 170	12,0
ASK 160-180	160 - 180	12,0
ASK 170-190	170 - 190	12,0
ASK 180-200	180 - 200	12,0
ASK 190-210	190 - 210	12,0
ASK 200-220	200 - 220	12,0
ASK 210-230	210 - 230	12,0
ASK 220-240	220 - 240	12,0
ASK 230-250	230 - 250	12,0
ASK 240-260	240 - 260	12,0
ASK 250-270	250 - 270	12,0
ASK 260-280	260 - 280	12,0
ASK 270-290	270 - 290	12,0
ASK 280-300	280 - 300	12,0
ASK 290-310	290 - 310	12,0

## Accesorii

SCHRAUBENDR	Șurubelniță flexibilă
-------------	-----------------------