

Caracteristici

| | |
|-----------------|-------------------------------|
| Tip constructiv | Bride de furtun fără șuruburi |
| Material | oțel crom nichelat inoxidabil |



Descriere

Brida de furtun CLIC este un element de legătură sigur pentru sistemele furtun - ștuț.

Articol

| Denumire | Domeniu de strângere (mm) | Lățime bandă (mm) |
|----------------|---------------------------|-------------------|
| CLIC 11.5-12.5 | 11,5 - 12,5 | 7,0 |
| CLIC 12-13 | 12,0 - 13,0 | 7,0 |
| CLIC 13-14 | 12,5 - 14,0 | 8,0 |
| CLIC 14-15 | 13,5 - 15,0 | 8,0 |
| CLIC 15-16 | 14,5 - 16,0 | 8,0 |
| CLIC 16-17 | 15,5 - 17,0 | 8,0 |
| CLIC 17-18 | 16,5 - 18,0 | 8,0 |
| CLIC 18-19 | 17,5 - 19,0 | 8,0 |
| CLIC 19-20 | 18,5 - 20,0 | 8,0 |
| CLIC 20-21 | 19,5 - 21,0 | 8,0 |
| CLIC 20.5-21.5 | 20,5 - 22,0 | 8,0 |
| CLIC 21.5-23 | 21,5 - 23,0 | 8,0 |
| CLIC 22.5-24 | 22,5 - 24,0 | 8,0 |
| CLIC 23.5-25 | 23,5 - 25,0 | 8,0 |
| CLIC 25.5-27 | 25,5 - 27,0 | 8,0 |
| CLIC 26.5-28 | 26,5 - 28,0 | 8,0 |

Accesorii

| | |
|------------|--------------------------|
| CLIC ZANGE | Clește pentru brida CLIC |
|------------|--------------------------|