WAS STRAHL

Furtun de apă construcții

Caracteristici



Caracteristici speciale	extrem de flexibil și de robust fără substanțe care ar putea afecta negativ aderența vopselei, fără agenți de separare, unsori rezistență scăzută la curgere
Strat interior	strat interior din EPDM neted, fără pori, negru
Inserţie	fire textile din material sintetic
Strat exterior	EPDM fără sensibilitate la ozon și radiații UV
Culoarea	negru
Temperatură min.	-40 °C
Temperatură max.	95 °C
Domeniu de temperaturi	Peakuri de temperatură până la 110°C
Medii	Apă

Indicaţie

Presiunea de lucru se raportează la temperatura ambiantă

Articol

Denumire	Țol	Ø interior (mm)	Grosimea peretelui (mm)	Presiune de lucru (bar)	Rază min. de îndoire (mm)	Lungimea rolelor (m)
WAS 10-3.5 STRAHL	3/8"	10	3,5	20,0	60	50
WAS 13-3 STRAHL	1/2"	13	3,0	20,0	80	40
WAS 16-3.5 STRAHL	5/8"	16	3,5	20,0	100	40
WAS 19-4 STRAHL	3/4"	19	4,0	20,0	120	40
WAS 25-4.5 STRAHL	1"	25	4,5	20,0	150	40
WAS 32-6 STRAHL	1.1/4"	32	6,0	20,0	200	50

În pofida controlului minuțios nu putem exclude eventualele informații eronate și nu garantăm pentru datele cuprinse.