


# K-PVDF-SCHLAUCH NATUR

PVDF tubing nature

**HANSA FLEX**

## Caracteristici

|                  |                                     |
|------------------|-------------------------------------|
| Utilizare        | resistant to a variety of chemicals |
| Strat interior   | PVDF                                |
| Strat exterior   | PVDF                                |
| Culoarea         | Natural                             |
| Temperatură min. | -40 °C                              |
| Temperatură max. | 150 °C                              |



## Informații suplimentare

- very good temperature resistance
- extremely high pressure resistance
- sterilisable
- non-combustible (to UL 94 V-O)
- very good UV resistance
- very low gas permeability
- excellent mechanical properties

## Articol

| Denumire       | Ø interior<br>(mm) | Ø exterior<br>(mm) | Grosimea peretelui<br>(mm) | Rază min. de îndoire<br>(mm) | Lungimea rolelor<br>(m) |
|----------------|--------------------|--------------------|----------------------------|------------------------------|-------------------------|
| K- 07 10 13 16 | 2,0                | 4,0                | 1,0                        | 60                           | 100                     |
| K- 07 10 13 17 | 4,0                | 6,0                | 1,0                        | 75                           | 100                     |
| K- 07 10 13 18 | 6,0                | 8,0                | 1,0                        | 85                           | 100                     |
| K- 07 10 13 19 | 8,0                | 10,0               | 1,0                        | 100                          | 100                     |
| K- 07 10 13 20 | 10,0               | 12,0               | 1,0                        | 125                          | 100                     |